



CMF / CRF Details

CMF ID: 2125

Install bicycle tracks

Description: Bicycle tracks are about 2-2.5 meters wide.

Prior Condition: No bike facilities

Category: Bicyclists

Study: [Bicycle Tracks and Lanes: a Before-After Study, Jensen, 2008](#)

Star Quality Rating:	
	<input type="text" value="5 Stars"/>

Crash Modification Factor (CMF)	
Value:	1.12
Adjusted Standard Error:	
Unadjusted Standard Error:	0.054

Crash Reduction Factor (CRF)	
Value:	-12 (This value indicates an increase in crashes)
Adjusted Standard Error:	
Unadjusted Standard Error:	4.25

Applicability

Crash Type:	All
Crash Severity:	K (fatal),A (serious injury),B (minor injury),C (possible injury)
Roadway Types:	Not Specified
Number of Lanes:	
Road Division Type:	
Speed Limit:	
Area Type:	
Traffic Volume:	5000 to 28000 <i>Average Daily Traffic (ADT)</i>
Time of Day:	All

If countermeasure is intersection-based

Intersection Type:	
Intersection Geometry:	
Traffic Control:	
Major Road Traffic Volume:	
Minor Road Traffic Volume:	

Development Details

Date Range of Data Used:	1976 to 2004
Municipality:	Copenhagen, Denmark
State:	
Country:	
Type of Methodology Used:	3
Sample Size Used:	

Before Sample Size Used:	77
After Sample Size Used:	77

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Dec-01-2009
Comments:	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.